

LITHIUM IRON PHOSPHATE BATTERY

ELECTRICAL PERFORMANCE

Nominal Voltage	12.8 V
Nominal Capacity	75 Ah
Capacity @ 15A	300 min
Energy	960 Wh
Resistance	≤18 mΩ @ 50% SOC
Self Discharge	<3% / Month
Cells	IFR26650EC

CHARGE PERFORMANCE

Recommended Charge Current	15 A
Maximum Charge Current	75 A
Recommended Charge Voltage	14.4 V (±.2V)
BMS Charge Cut-Off Voltage	15.4 V (±.2V) 3.65/Cell (±.2)
Reconnect Voltage	14.4 V (±.2V) 3.6V/Cell (±.2)
Balancing Voltage	14.4 V (±.2V) 3.6V/Cell (±.2)
Maximum Batteries in Series	4

DISCHARGE PERFORMANCE

Maximum Continuous Discharge Current	75 A
Peak Discharge Current	160 A (3 s)
BMS Discharge Cut-Off Current	240 A ± 5 A (31 ms)
Recommended Low Voltage Disconnect	11 V (2.75V/Cell)
BMS Discharge Cut-Off Voltage	8.0 V (2s) (2.0V/Cell)
Reconnect Voltage	10 V (±.2V) 2.5V/Cell (±.2)
Short Circuit Protection	250 ~ 500 μs



MECHANICAL PERFORMANCE

Dimension (L x W x H)	260 x 168 x 218 mm 10.2 x 6.6 x 8.6"
Approx. Weight	20.5 lbs (9.3 kg)
Terminal Type	T11
Terminal Torque	80 - 100 in-lbs (9 - 11 N-m)
Case Material	ABS
Enclosure Protection	IP65


TEMPERATURE PERFORMANCE

Discharge Temperature	-4 ~ 131 °F (-20 ~ 55 °C)
Charge Temperature	32 ~ 113 °F (0 ~ 45 °C)
Storage Temperature	23 ~ 95 °F (-5 ~ 35 °C)
BMS High Temperature Cut-Off	149 °F (65 °C)
Reconnect Temperature	131 °F (55 °C)

COMPLIANCE

Certifications	CE (battery) UN38.3 (battery) UL1642 & IEC62133 (cells)
Shipping Classification	UN 3480, CLASS 9





OUTLINE DIMENSION



L mm(")	W mm(")	H mm(")	HT mm(")
260 (10.2)	168 (6.6)	210 (8.3)	218 (8.6)

Performance may vary depending on application. All specifications are subject to change without prior notice to the user. This data is for evaluation purposes only. No guarantee is intended or implied by this data. For clarification and updated information, please contact us.

PERFORMANCE CHARACTERISTICS



FEATURES & BENEFITS



High cycle life

>3500 cycles @80% DOD for effectively lower total cost of ownership.



Longer service life

Low maintenance batteries with stable chemistry.



Built in circuit protection

Battery Management System (BMS) is incorporated to protect against abuse.



Better storage

Up to 6 months thanks to its extremely low self discharge (LSD) rate and no risk of sulfation.



Quickly recharge

Save time and increase productivity with less down time thanks to superior charge/discharge efficiency.



Extreme heat tolerance

Suitable for use in a wider range of applications where ambient temperature is unusually high: up to +55°C.



Lightweight

Lithium batteries provide more wh/lb while also being up to 1/3 the weight of its SLA equivalent.

APPLICATIONS

Lithium Iron Phosphate can be used in most applications that use Lead Acid, GEL or AGM type batteries. Suitable applications include:

- RV
- Marine
- Golf Cart
- Off Road/Overland Vehicles
- Solar Storage
- Remote Monitoring

CAUTIONS

- Do NOT short circuit, reverse polarity, crush or disassemble.
- Do NOT heat or incinerate.
- Do NOT immerse in any liquid.
- Store at 30~50% SOC. Recharging every 3 months is recommended. The storage area should be clean, cool, dry and ventilated.

Performance may vary depending on application. All specifications are subject to change without prior notice to the user. This data is for evaluation purposes only. No guarantee is intended or implied by this data. For clarification and updated information, please contact us.

